

## Pressure Switch Enquiry Form

Please complete the details below and either fax this form to (+44) 01255 862014 or e-mail to [sales@assemtech.com](mailto:sales@assemtech.com)

Name

Company

Address

Telephone

Fax

E-mail

Part Number    \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

Qty

Example **SQ24B-ANC-2A1**

Pressure switch	<b>SQ Series</b>	Hex length <b>24mm / 27mm</b>																		
Body material	<b>B = Brass    S = Stainless Steel grade 316    Z = Zinc plated steel</b>																			
Contact type	<b>A = Normally open contacts    B = Normally closed contacts</b> <b>S = Single pole double throw (SQ 27 only)</b>																			
Diaphragm material	<b>N = Nitrile (standard -30+100°C)    V = VITON (-5+120°C)    E = EPDM (-30+120°C)</b>																			
Connection fitting	<b>S = Screw terminals    T = Tag (spade terminal)    C = DIN Cap</b>																			
Screw thread	<table border="0"> <tr> <td><b>1 = M10X1 (tap 1°)</b></td> <td rowspan="9">Adjustable</td> <td><b>F1 = 0.2 Bar</b></td> </tr> <tr> <td><b>2 = M10X1</b></td> <td><b>F2 = 1.1 Bar</b></td> </tr> <tr> <td><b>3 = M12X1.5</b></td> <td><b>F3 = 5 Bar</b></td> </tr> <tr> <td><b>4 = 1/8" PT</b></td> <td><b>F4 = 50 Bar</b></td> </tr> <tr> <td><b>5 = 1/4" PT</b></td> <td><b>A1 = 0.2-1 Bar</b></td> </tr> <tr> <td><b>6 = 1/8" G</b></td> <td><b>A2 = 1-19 Bar</b></td> </tr> <tr> <td><b>7 = 1/4" G</b></td> <td><b>A3 = 20-50 Bar</b></td> </tr> <tr> <td><b>8 = 1/8" NPT</b></td> <td><b>A4 = 51-100 Bar</b></td> </tr> <tr> <td><b>9 = 1/4" NPT</b></td> <td></td> </tr> </table>	<b>1 = M10X1 (tap 1°)</b>	Adjustable	<b>F1 = 0.2 Bar</b>	<b>2 = M10X1</b>	<b>F2 = 1.1 Bar</b>	<b>3 = M12X1.5</b>	<b>F3 = 5 Bar</b>	<b>4 = 1/8" PT</b>	<b>F4 = 50 Bar</b>	<b>5 = 1/4" PT</b>	<b>A1 = 0.2-1 Bar</b>	<b>6 = 1/8" G</b>	<b>A2 = 1-19 Bar</b>	<b>7 = 1/4" G</b>	<b>A3 = 20-50 Bar</b>	<b>8 = 1/8" NPT</b>	<b>A4 = 51-100 Bar</b>	<b>9 = 1/4" NPT</b>	
<b>1 = M10X1 (tap 1°)</b>	Adjustable	<b>F1 = 0.2 Bar</b>																		
<b>2 = M10X1</b>		<b>F2 = 1.1 Bar</b>																		
<b>3 = M12X1.5</b>		<b>F3 = 5 Bar</b>																		
<b>4 = 1/8" PT</b>		<b>F4 = 50 Bar</b>																		
<b>5 = 1/4" PT</b>		<b>A1 = 0.2-1 Bar</b>																		
<b>6 = 1/8" G</b>		<b>A2 = 1-19 Bar</b>																		
<b>7 = 1/4" G</b>		<b>A3 = 20-50 Bar</b>																		
<b>8 = 1/8" NPT</b>		<b>A4 = 51-100 Bar</b>																		
<b>9 = 1/4" NPT</b>																				
Optional Socket Type	<b>D = DT04-2P    A = 250 Type</b>																			
Socket wiring	<b>1 = 3mm PVC (2P)    2 = 3mm PVC (2P) with wrap up sheath</b>																			
Add <b>(XX)</b> to end	<b>3 = 6.4mm PE Cable    4 = 3mm PVC (2P) with heat shrink sheath</b>																			
Cap only part number	<b>SQA-1130</b>																			